

**TECHNICAL DATA** 

# Fluke TL71 Premium Test Lead Set



(€.∰.,

## **Key features**

- Comfort grip probes with right-angle test leads, equipped with WearGuard™ indicator for damage detection
- Silicone-insulated leads have superior flexibility in cold temperatures and resistance to high temperatures
- CAT II 1000 V, 10 A rated, When the protective caps are placed on the leads, the ratings jump up to CAT IV 600 V, CAT III 1000 V
- see compatible products below

### Product overview: Fluke TL71 Premium Test Lead Set

The Fluke TL71 Premium Multimeter Test Lead Set is a pair of comfort grip probes (red and black) with flexible siliconeinsulated, right-angle test leads. These distinctive comfort grip probes are heat and cold resistant.

As with all Fluke products, these test leads undergo a battery of safety tests to be rated at:

CAT II 1000 V, 10 A rating

CAT III 1000 V, CAT IV 600V with protective cap

The WearGuard<sup>™</sup> test lead indicator shows wear and tear easier. It exposes a contrasting color when the leads are damaged and need to be replaced. Silicone-insulated leads have superior flexibility in cold temperatures and resistance to high temperatures.

The Fluke TL71 Premium Test Leads are compatible with all instruments that accept standard 4 mm (0.16 in) shrouded



banana connectors. Some of the compatible tools include:

Fluke 902 FC True-RMS HVAC Clamp Meter

Fluke 87V Industrial Multimeter

Fluke 115 Field Technicians Digital Multimeter

Fluke 787B ProcessMeter™

These test leads come with a one-year warranty.

#### Specifications: Fluke TL71 Premium Test Lead Set

Lead Length	1.2 (4 ft), 2mm diameter probe tip
Category Rating	CAT II 1000 V, CAT III 1000 V, CAT IV 600 V, 10 A max
Operating temperature	-20°C to 55°C (-4°F to 131°F), 90 % RH altitude: 2000 m (6,562 ft)



#### **Ordering information**



#### Fluke TL71

Test Lead Set

- One pair (red, black) comfort grip probes with silicone insulated, right-angle test leads
- Recommended for  $\mu V$  measurements
- CAT II 1000 V, 10 A rating
- CAT III 1000 V, CAT IV 600V only with protective cap
- One year warranty



#### Fluke. Keeping your world up and running.®

Fluke Europe B.V. P.O. Box 1186 5602 BD Eindhoven The Netherlands www.fluke.com/en ©2024 Fluke Corporation. All rights reserved. Data subject to alteration without notice. 09/2024

Modification of this document is not permitted without written permission from Fluke Corporation.

For more information call:

In Middle East/Africa

+31 (0)40 267 5100